

BONESTOCK MIDSIZE FWD RULES

These rules are plain and simple, cut and dry!!! What is said below is exactly what you can do and nothing else. Don't try and do anything else cause most likely you will just be loaded!

(FWD and RWD 4 or 6 cyl cars only! 110 fwd and 108 rwd wheelbase and under!

Car must be stripped of all internals and outside plastic as well as all windows. Dash may stay in the car.

Roof Sign Required

FRAMES:

NO welding on frames or holes whatsoever.

CAGE

Full 4 point cage may be applied to your car for drivers safety must be floating (MINIMUM OF SEAT AND DRIVERS DOOR BAR) 3x3 material no bigger.

Tank can be mounted to back of cage bar or bolted through floor. Tank protector must extend Straight up and down. From tank . IF IN FRONT OF REAR AXLE CAN BE LEFT UNDER CAR.

1 front windshield bars must be added. 9 wire, 2x2 straps, chain

SUSPENSION

100 % stock suspension. Don't touch it.

NOTHING can be welded to the strut!

DOORS, HOOD, TRUNK

Drivers door may be welded shut.

Every other seam can have :

3 spots of 9 Wire double wrapped

3/8 chain

Hood and Trunk must have 12x12 hole in them.

No duck tape on doors

Front body/subframe mounting area

2 all thread may run through your front body mount up through hood to secure hood. No bigger than **3/4 in** all thread.

Front subframe may not be welded to body!

NO Strut blocks

NO extra body mounts

BUMPERS

Factory bumper to car only. (no extra welding)

Acception: cars with plastic bumper may use a different steel fwd replacement steel bumper. Welded on with 1 pass only.

TIRES

DOT TIRES ONLY

Rears must be donuts or stock to vehicle.

MISC

Aftermarket harness and computer ok, NO Carb conversions

Aftermarket steering, peddles, shifters, Headers can be used.

Gas tank in front of rear axle may stay.